
ಭಾ. ಕೃ. ಅನು. ಪ – ಭಾರತೀಯ ತೋಟಗಾಲಿಕಾ ಸಂಶೋಧನಾ ಸಂಸ್ಥೆ ಹೆಸರಥಟ್ಟ ಕೆರೆ ಅಂಜೆ, ಖೆಂಗಚೂರು–560 089



ICAR-Indian Institute of Horticultural Research Hesaraghatta Lake Post, Bengaluru - 560 089

EPABX: 080-23086100 Extn: 218 & 217 FAX: 080-28466291 – Email: purchase.iihr@icar.gov.in

F.No.5-102/2-119/2024-25/SP-CHES-Bhuwaneshwar/326502

Dated: 17.09.2024

NOTICE FOR INVITING TENDER THROUGH E-PROCUREMENT

Online Bids are invited from interested firms under <u>Two bid system (Technical bid/financial bid)</u> for :Construction of Office building (14.50 mtr x 7.5 mtr) with staircase and electrical installation at ICAR- IIHR,CHES-Bhubaneswar, Odisha 751019. Manual bids will not be entertained.

Tender documents may be downloaded from e-procurement website of CPPP https://eprocure.gov.in/eprocure/app as per the schedule given in CRITICAL DATE SHEET as under:

CRITICAL DATE SHEET

Tender No.	F.No. 5-102/2-119/2024-25/SP-CHES- Bhuwaneshwar/326502
Name of Organization	ICAR-INDIAN INSTITUTE OF HORTICULTURAL RESEARCH,
	Hessaraghatta Lake Post, Bangalore
Date and Time for Issue/Publishing	17.09.2024 at 04:00 PM
Document Download/Sale Start Date	17.09.2024 at 04:00 PM
and Time	
Bid Submission start Date and Time	17.09.2024 at 04:00 PM
Bid Submission End Date and Time	07.10.2024 at 03:00 PM
Date and Time for Opening of Technical Bids	09.10.2024 at 10:00 AM
Address for Communication	Senior Administrative Officer (Purchase), IIHR,
	Hessaraghatta Lake Post, Bangalore

Sd/-

CHIEF ADMINISTRATIVE OFFICER(SG)

Annexure-I

INSTRUCTIONS FOR ONLINE BID SUBMISSION

- The Tender form/bidder documents may be downloaded from the https://eprocure.gov.in/eprocure/app. Online submission of Bids through Central Public Procurement Portal (https://eprocure.gov.in/eprocure/app) is mandatory. Manual/Offline bids shall not be accepted under any circumstances.
- 2. Tenderers/bidders are requested to visit the website https://eprocure.gov.in/eprocure/app regularly. Any changes/modifications in tender enquiry will be intimated by corrigendum through this website only.
- 3. In case, any holiday is declared by the Government on the day of opening, the tenders will be opened on the next working day at the same time. The Council reserves the right to accept or reject any or all the tenders.
- 4. The Firms are required to deposit (in original) EMD of Rs.52,000/- in the shape of Demand Draft in favour of THE DIRECTOR, ICAR, UNIT-IIHR payable at Bangalore may be addressed to Senior Administrative Officer (Purchase), IIHR, Hesaraghatta Lake Post, Bangalore-560089 on or before 07.10.2024 as mentioned in the Critical Date Sheet.
- 5. Please note that only online Bids will be accepted.
- 6. Bidders need not to come at the time of Technical as well as Financial bid opening at IIHR. They can view live bid opening after login on CPPP e-procurement portal at their remote end. If any dispute arises, Within Bengaluru Jurisdiction only.
- 7. The firms are also required to upload copies of the following documents for Technical eligibility and Evaluation:-

Technical Bid

1. No EMD exemption is given for MSME/ Udyog Aadhar or NSIC and other firms

- 2. Scanned copy of the documents Registered with PWD/CPWD/MES/Railways.
- 3. PAN Card copy
- 4. GST Number with Registration Certificate
- **5.** Bank details of the firm.
- **6.** Income Tax Returns for the last three years (2021-22,2022-23,2023-24).
- 7. Profit and loss account & Balance Sheet which are audited & duly certified by the Chartered Accountant for the last three years (2021-22,2022-23,2023-24).

- 8. Turnover of the business should be <u>Rs.75.00 Lakhs</u> per year (2021-22,2022-23,2023-24). And Chartered Accountant certified profit and Loss account; Balance sheet to this effect may be enclosed.
- 9. Scanned copy of work/supply order for having successfully completed similar works during last <u>5 years</u> ending last day of month previous to the one in which bids are invited should be either of the following:
- a) Three similar completed works costing not less than the amount equal to 40(forty) percent of the estimated cost of Rs.10,25,665/- each

or

b) Two similar completed works costing not less than the amount equal to 50(Fifty) percent of the estimated cost of Rs.12,82,000/- each

or

c) One similar completed works costing not less than the amount equal to 80 (eighty) percent of the estimated cost of Rs.20,51,000/- each

(Similar work: Construction of Building)

- 10. Tender acceptance letter (Annexure-V) is mandatory.
- 11. Latest copies of the GST returns for six months (January to June 2024)

• Financial Bid:-

- a) Price Bid as BOQ XXX.xls
- b) Evaluation criteria: Tender will be awarded to the lowest quoted Firm among those firms qualified in the Technical Bid. In case, two or more firms quote the same amount in r/o all the items work together as a whole, then the tender will be awarded to the Firm which has got more average turnover in the last 3 years, based on IT returns/Profit & Loss account/Turnover duly certified by the CA and uploaded along with Tender through CPP.

Sd/-CHIEF ADMINISTRATIVE OFFICER(SG)

Terms & Conditions

- 1. The tenderer shall quote rates, which will include the supply, installation & other incidental charges.GST, if any, should be indicated separately.
- 2. The rates should be quoted as per the BOQ uploaded on the CPP Portal (reference may be obtained from Annexure-III). GST, if any, should be indicated separately. It must be noted that the contract shall be awarded to the firm which fulfils all the required terms and conditions and remains L-I for **Total cost**.
- 3. The firm must also possess valid PAN No. & GST registration number and a copy of the same must also be enclosed with the tender document.
- 4. Latest copies of the GST returns for six month(January to June 2024)
- 5. Copy of Income Tax Return Statement may be furnished for the Financial year 2021-22, 2022-23, & 2023-24.
- 6. Profit and loss account & Balance Sheet which are audited & duly certified by the Chartered Accountant for the last three years (2021-22, 2022-23, & 2023-24).
- 7. Turnover of the business should be <u>Rs.75.00 Lakhs</u> per year (2021-22, 2022-23, & 2023-24). And Chartered Accountant certified profit and Loss account; Balance sheet to this effectmay be enclosed.
- 8. Modification in the tender documents after the closing date is not permissible.
- 9. The successful firm shall **commence work** within 10 days from the date of confirmed **work order** and if the work not completed in time then EMD shall be forfeited. The rates quoted shall be valid for one year from the date of opening of tender.
- 10. The contractor/bidder or his representative may contact the undersigned at **Tel. No. 080-23086100 Extn: 217 & 211** for any further clarification. No variation in terms and quality of the items/specifications shall be entertained or else EMD/Security deposit shall be forfeited.
- 11. The bidder is advised to visit the site of works at his own expenses and obtain all information that may be necessary for preparing the quotation. Submission of quotation is acceptance by the tenderer that he has inspected the site or he is aware of all conditions.
- 12. The Director, ICAR-IIHR, shall have the right to reject all or any of the offers, accept more than one offer, and assign part of the job without assigning any reason.
- 13. Merely quoting of lowest rates does not mean that order shall be given to that firm. The competent authority will finally decide on the basis of quality & performance of past installations.
- 14. The Firms are required to deposit (in original) an Earnest Money Deposit of Rs.52,000/amount mentioned against item in the form of Demand Draft from any of the Commercial
 Bank in favour of THE DIRECTOR, ICAR, UNIT-IIHR payable at Bangalore may be
 address to Senior Administrative Officer (Purchase), IIHR, Hessaraghatta Lake Post,
 Bangalore-560089 on or before 07.10.2024 as mentioned in the Critical Date Sheet. No
 quotation shall be considered without the earnest money deposit. Demand draft drawn in
 favour of any officer other than 'THE DIRECTOR, ICAR UNIT-IIHR payable at Bangalore'
 will not be accepted and the tender will be rejected. The earnest money will be refunded only
 after the finalization of the procurement and no interest will be paid on earnest money. The
 request letter for refund of EMD & performance security is to be submitted by the firm.
- 15. Rates once finalized will not be enhanced/reduced during the currency of the contract.
- 16. In case, the successful bidder shows inability at any stage, after the contract is finalized and awarded, for whatsoever reason(s), to honour the contract, the earnest money /performance security deposited would be forfeited.
- 17. The Director, ICAR-IIHR reserves the right to cancel the contract at any time during the currency period of the contract without giving any reason.

- 18. The firm, to whom the tender will be awarded, will have to deposit the performance security equal to 3% of the total quoted amount at which the Tender will be awarded within 21 days from the date of receipt of work order and the same will be retained during the Defect liability period(warranty) of One year. In the sense, for any material and execution defects, the firm has to set right the defects within 10 working days and maintain the said work. If the services are not found to be satisfactory, the performance security is liable to be forfeited. No interest will be paid on performance security.
- 19. If any dispute(s) arises between IIHR and the firm with reference to the contract, IIHR will decide it and its decision will be binding on the firms.
- 20. Bid Validity: 90 days
- 21. Payment:- No advance or part payment will be given. The payment will be released after satisfactory completion of the work and certificate from the Indentor/Engineer. The payment shall be arranged by ICAR-IIHR, CHES, BHUBANESWAR.
- 22. The supplier/firm has to submit the GST return for having remitted the GST amount paid by the institute to the concerned authority within 30 days from receipt of payment from IIHR, otherwise their EMD and SD/PS will not be released and such firms shall be blocklisted.
- 23. No EMD exemption is given for MSME/ Udyog Aadhar or NSIC and other firms.
- 24. Work Completion: 60 days from the date of issue of work order.
- 25. GST extra as applicable should be indicated separately in the column provided. Otherwise such quotes will be rejected.

Payment Terms: In order to facilitate for speedy settlement of payment you are requested to furnish the following details as below:

- 1. Name of the firm:
- 2. Name of the Bank:
- 3. IFSC Code of Bank:
- 4. Name of the Account & Account No.:
- 5. Branch Code:
- 6. Amount to be paid:
- 7. E-mail address of the party:
- 8. GST No. and Pan No. Copies

	'Terms & Conditions are acceptable
Dated	(Authorized signatory of the firm)

(Reference for BOQ) (To be quoted in format provided on CPP Portal)

Price bid for: Construction of office building (14.5m x 7.5 m) with staircase and electrical installation at ICAR-IIHR, CHES-Bhubaneswar, Odisha 751019.

Sl. No.	Name of item	Quantity	Per unit price* (in figures/words) (as per BOQ)
01	Construction of office building (14.5m x 7.5 m) with staircase and electrical installation at ICAR-IIHR,CHES-Bhubaneswar, Odisha 751019 *		

*Annexure-VIII

- Items should be of reputed make and suitable for high end elite users
- GST extra as applicable should be indicated separately in the column provided. Otherwise such quotes will be rejected.
- ICAR-IIHR, CHES-Bhubaneswar, Odisha 751019.

Note: The above mentioned Financial Proposal/Commercial bid format is provided as BoQ_XXXX/xls along with this tender document at https://eprocure.gov.in/eprocure/app. Bidders are advised to download this BoQ_XXXX.xls as it is and quote their offer/rates in the permitted column and upload the same in the Financial bid. **Bidder shall not tamper/modify downloaded price bid template in any manner**. In case if the same is found to be tempered/modified in any manner, tender will be completely rejected and EMD would be forfeited and tenderer is liable to be banned from doing business with IIHR.

EPABX: 080-23086100 Extn: 218 & 217

FAX: 080-28466291 - Email: purchase.iihr@icar.gov.in



ICAR-INDIAN INSTITUTE OF HORTICULTURAL RESEARCH

HESSARAGHATTA LAKE POST, BANGALORE-560 089

Name of	f the Firm	
Register	red/Postal Address	
1	Permanent Account Number (PAN)	
2	GST Registration No.	
3	Bank Details	
a	Bank Name	
b	Branch Address	
С	Account Number	
d	Type of account (current/saving) MICR No.	
e	IFSC Code	
Date:		Name of the Authorized Signatory
Place:		Stamp & Signature

TENDER ACCEPTANCE LETTER

(To be given on Company Letter Head)

T	Date:
To,	ne Director,
	CAR-IIHR,
	esaraghatta Lake Post,
	angalore-560089.
Sub:	Acceptance of Terms & Conditions of Tender.
Tende	r Reference No
Name	of Tender/Work:
Dear S	Sir,
1.	I/ We have downloaded/obtained the tender document(s) for the above mentioned' Tender/work' from the web site(s) namely:
	As per your advertisement, given in the above mentioned website(s).
2.	I/We hereby certify that I/We have read the entire terms and conditions of the tender documents from Page No (including all documents lime annexure(s), schedule(s), etc) which form part of the contract agreement and I/We shall abide hereby the terms/conditions/clauses contained therein.
3.	The corrigendum(s) issued from time to time by your department/organization too have also been taken into consideration, while submitting this acceptance letter.
4.	I/we hereby unconditionally accept the tender conditions of above mentioned tender documents/corrigendum(s) in its totality/entirely.
5.	I/we do hereby declare that our Firm has not been black-listed/debarred by any Govt. Department/Public sector undertaking.
6.	I/we certify that all information furnished by our Firm is true & correct and in the event that the information is found to be incorrect/untrue or found violated, then your department/organization shall without giving any notice or reason therefore or summarily reject that bid or terminate the contract, without prejudice to any other rights or remedy including the forfeiture of the full said earnest money deposit absolutely.

Yours Faithfully,

(Signature of the Bidder, with Official Seal)

INSTRUCTIONS FOR ONLINE BID SUBMISSION

The bidders are required to submit soft copies of their bids electronically on the CPP Portal, using valid Digital Signature Certificates. The instructions given below are meant to assist the bidders in registering on the CPP Portal, prepare their bids in accordance with the requirements and submitting their bids online on the CPP Portal.

More information useful for submitting online bids on the CPP Portal may be obtained at https://eprocure.gov.in/eprocure/app.

REGISTRATION

- Bidders are required to enroll on the e-Procurement module of the Central Public Procurement Portal (URL https://eprocure.gov.in/eprocure/app.) by clicking on the link 'Online bidder Enrollment' on the CPP Portal which is free of charge.
- As part of the enrolment process, the bidders will be required to choose a unique username and assign a password for their accounts.
- Bidders are advised to register their valid email address and mobile numbers as part of the registration process. These would be used for any communication from the CPP Portal.
- Upon enrolment, the bidders will be required to register their valid Digital Signature Certificate (class II or Class III certificates with signing key usage) issued by any certifying authority recognized by CCA India (e.g. Sify/nCode/eMudhra etc.) with their profile.
- Only one valid DSC should be registered by a bidder. Please note that the bidders are responsible to ensure that they do not lend their DSC's to others which may lead to misuse.
- Bidder then logs in to the site through the secured log-in by entering their users ID/password and the password of the DSC/e-Token.

SEARCHING FOR TENDER DOCUMENTS

- There are various search options built in the CPP Portal. To facilitate bidders to search active tenders by several parameters. These parameters could include Tender ID, Organization Name, Location, Date, Value etc. There is also an option of advanced search for tenders, wherein the bidders may combine a number of search parameters such as Organization Name, Form of Contract, Location, Date, Other keywords etc. to search for a tender published on the CPP Portal.
- Once the bidders have selected the tenders they are interested in, they may download the
 required documents/tender schedules. These tenders can be moved to the respective 'My
 Tenders' folder. This would enable the CPP Portal to intimate the bidders through SMS/email in case there is any corrigendum issued to the tender document.
- The bidder should make a note of the unique Tender ID assigned to each tender, in case they want to obtain any clarification/help from the Helpdesk.

PREPARATION OF BIDS

 Bidder are requested to visit the site at the Institute ICAR-IIHR, CHES-Bhubaneswar, Odisha 751019 and if required have consultation with Senior Engineer, ICAR-CIFA, Bhubaneswar, before preparing the bid clarify the doubts and understand the requirements.

9

- Bidder should take into account any corrigendum published on the tender document before submitting their bids.
- Please go through the tender advertisement and the tender document carefully to understand the documents required to be submitted as part of the bid. Please note the number of covers in which the bid documents have to be submitted, the number of documents- including the names and content of each of the document that need to be submitted. Any deviations from these may lead to rejection of the bid.
- Bidder, in advance, should get ready the bid documents to be submitted as indicated in the tender document/schedule and generally, they can be in PDF/XLS/RAR/DWF/JPG formats. Bid documents may be scanned with 100 dpi with black and white option which helps in reducing size of the scanned document.
- To avoid the time and effort required I uploading the same set of standard documents which are required to be submitted as a part of every bid, a provision of uploading such standard documents (e.g. PAN card copy, annual reports, auditor certificates etc.) has been provided to the bidders. Bidders can use 'My Space' or 'Other important Documents' area available to them to upload such documents. These documents may be directly submitted from the 'My Space' area while submitting a bid, and need not be uploaded again and again. This will lead to a reduction in the time required for bid submission process.

SUBMISSION OF BIDS

- Bidder should log into the site will in advance for bid submission so that they can upload the bid in time i.e. on or before the bid submission time. Bidder will be responsible for any delay due to other technical issues.
- The bidder has to digitally sign and upload the required bid documents one by one as indicated in the tender document.
- Bidder has to select the payment option as 'offline' to pay the tender fee/EMD as applicable and enter details of the instrument.
- Bidder should prepare the EMD as per the instructions specified in the tender document. The
 original should be posted/couriered/given in person to the concerned official, latest by the
 last date of bid submission or as specified in the tender documents. The details of the
 DD/any other accepted instrument, physically sent, should tally with the details available in
 the scanned copy and the data entered during bid submission time. Otherwise the uploaded
 bid will be rejected.
- Bidders are requested to note that they should necessarily submit their financial bids in the Format provided and no other format is acceptable. If the price bid has been given as a standard BoQ format with the tender document, then the same is to be downloaded and to be filled by all the bidders. Bidders are required to download the BoQ file, open it and complete the white coloured (unprotected) cell with their respective financial quotes and other details (such as name of the bidder). No other cells should be changed. Once the details have been completed, the bidder should save it and submit it online, without changing the filename. If the BoQ file is found to be modified by the bidder, the bid will be rejected.
- The server time (which is displayed on the bidders' dashboard) will be considered as the standard time for referencing the deadlines for submission of the bids by the bidders, opening of bids etc. The bidders should follow this time during bid submission.
- All the documents being submitted by the bidders would be encrypted using PKI encryption techniques to ensure the secrecy of the data. The data entered cannot be viewed by unauthorized persons until the time of bid opening. The confidentiality of the bids is maintained using the secured Socket Layer 128 bit encryption technology. Data storage

encryption of sensitive fields is done. Any bid document that is uploaded to the server is subjected to symmetric, encryption using a system generated symmetric key. Further this key is subjected to asymmetric encryption using buyers/bid openers public keys. Overall, the uploaded tender documents become readable only after the tender opening by the authorized bid openers.

- The uploaded tender documents become readable only after the tender opening by the authorized bid openers.
- Upon the successful and timely submission of bids (i.e. after clicking 'Freeze Bid Submission' in the portal), the portal will give a successful bid submission message and a bid summary will be displayed with the bid no. and the date and time of submission of the bid with all other relevant details.
- The bid summary has to printed and kept as an acknowledgement of the submission of the bid.

ASSISSTANCE TO BIDDERS

- Any queries relating to the tender documents and the terms and conditions contained therein should be addressed to the Tender Inviting Authority for a tender or the relevant contract person indicated in the tender.
- Any queries relating to the process of online bid submission or queries relating to CPP Portal in general may be directed to the 24x7 CPP Portal Helpdesk.

Annexure-VII

Details of Works & EMD

S1.	Purchase of item	Qty	Earnest	File. No. for reference
			Money in	
No.			INR	
	Construction of office building (14.5m x			
	7.5 m) with staircase and electrical			
	installation atICAR-IIHR,CHES-			
	Bhubaneswar, Odisha-751019**			
		01		
01		UNIT	Rs.52,000/-	F.No. 5-102/2-119/2024-
				25/SP-CHES-
				Bhuwaneshwar/326502

Note:

- 1) EMD defined on to the Portal is MINIMUM. Bidder has to submit the EMD as per item for which quoting for.
- 2) No EMD exemption is given for MSME/ Udyog Aadhar or NSIC and other firms

^{*} ICAR-IIHR, CHES-Bhubaneswar, Odisha 751019.

Annexure-VIII

$\frac{\text{TECHNICAL SPECIFICATION FOR: }}{\text{STAIRCASE AND ELECTRICAL INSTALLATION ATICAR-IIHR, CHES-BHUBANESWAR, ODISHA-751019}}{\text{STAIRCASE AND ELECTRICAL INSTALLATION ATICAR-IIHR, CHES-BHUBANESWAR, ODISHA-751019}}}$

Description of items	Qty	Unit
Earth work in excavation by mechanical means (Hydraulic excavator) /manual means in		
dressing of sides and ramming of bottoms, lift up to 1.5 m, including getting out the		
	10 37	
Wall:12./Olli x 0.00lli x 0./Olli		2
	15.70	m3
consolidating and dressing complete.		
4 x 1.20m x 1.20m x 0.30	1.73	
12.70m x 0.60m x 0.10m	0.76	
7.00X2.50MX0.50M	8.75	
	11.24	m3
Providing and laying in position cement concrete of specified grade excluding the cost of		
	0.86	
7 A 1.20HI A 1.20HI A U.13HI	0.00	
12.70	0.76	
12./UIII X U.OUIII X U.1UIII	0.76	
7.70m x 2.50m x 0.10m	1.75	
	2 27	m3
	3.37	1113
Providing and laying in position specified grade of reinforced cement concrete, excluding		
	0.75	
4 x 1.20m x 1.20m x 0.10m	0.57	
4 x 0.60m x 0.60m x 0.50m	0.72	
4 x 0.50m x 0.40m x 2.00m	1.60	
	2.89	m3
Reinforced cement concrete work in walls (any thickness) including attached pilasters		
4nos x 0.50m x 0.40m x 3.00m	2.40	
10nos x 0.50m x 0.40m x 3.00m	6.00	
·	Ì	1
	8.40	m3
Reinforced cement concrete work in beams, suspended floors, roofs having slope up to 15"	8.40	m3
Reinforced cement concrete work in beams, suspended floors, roofs having slope up to 15" landings, balconies, shelves, chajjas, lintels, bands, plain window sills, staircases and spiral	8.40	m3
	foundation trenches or drains (not exceeding 1.5 m in width or 10 sqm on plan), including dressing of sides and ramming of bottoms, lift up to 1.5 m, including getting out the excavated soil and disposal of surplus excavated soil as directed, within a lead of 50 m. All kinds of soil Coi: 4 x 1.20m x 1.20m x 1.80m Wall:12.70m x 0.60m x 0.70m Supplying and filling in plinth with sand under floors, including watering, ramming, consolidating and dressing complete. 4 x 1.20m x 1.20m x 0.30 12.70m x 0.60m x 0.10m 7.00X2.50MX0.50M Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level:1:4:8 (1 Cement: 4 coarse sand (zone-III): 8 graded stone aggregate 40 mm nominal size) 4 x 1.20m x 1.20m x 0.15m 12.70m x 0.60m x 0.10m 7.70m x 2.50m x 0.10m Providing and laying in position specified grade of reinforced cement concrete, excluding the cost of centering, shuttering, finishing and reinforcement - All work up to plinth level:1:1.5:3 (1 cement: 1.5 coarse sand (zone-III): 3 graded stone aggregate 20 mm nominal size) 4 x 1.20m x 1.20m x 0.10m 4 x 0.60m x 0.60m x 0.50m Reinforced cement concrete work in walls (any thickness), including attached pilasters, buttresses, plinth and string courses, fillets, columns, pillars, piers, abuttments, posts and struts etc. above plinth level up to floor five level, excluding cost of centering, shuttering finishing and reinforcement: 1:1.5:3 (1 cement: 1.5 coarse sand(zone-iII): 3 graded stone aggregate 20 mm nominal size) 4 nos x 0.50m x 0.40m x 3.00m	foundation trenches or drains (not exceeding 1.5 m in width or 10 sqm on plan), including dressing of sides and ramming of bottoms, lift up to 1.5 m, including getting out the excavated soil and disposal of surplus excavated soil as directed, within a lead of 50 m. All kinds of soil Col: 4 x 1.20m x 1.20m x 1.80m Wall: 12.70m x 0.60m x 0.70m 5.33 15.70 Supplying and filling in plinth with sand under floors, including watering, ramming, consolidating and dressing complete. 4 x 1.20m x 1.20m x 0.30 1.73 12.70m x 0.60m x 0.10m 7.00X2.50MX0.50M 8.75 I1.24 Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level:1:4:8 (1 Cement: 4 coarse sand (20ne-III): 8 graded stone aggregate 40 mm nominal size) 4 x 1.20m x 1.20m x 0.10m 7.70m x 0.60m x 0.10m 1.75 Providing and laying in position specified grade of reinforced cement concrete, excluding the cost of centering, shuttering, finishing and reinforcement - All work up to plinth level:1:1.5:3 (1 cement: 1.5 coarse sand (20ne-III): 3 graded stone aggregate 20 mm nominal size) 4 x 1.20m x 1.20m x 0.10m 0.57 4 x 0.60m x 0.60m x 0.50m 1.60 2.89 Reinforced cement concrete work in walls (any thickness), including attached pilasters, buttresses, plinth and string courses, fillets, columns, pillars, piers, abuttments, posts and struts etc. above plinth level up to floor five level, excluding cost of centering, shuttering finishing and reinforcement: 1:1.5:3 (1 cement: 1:5 coarse sand(20ne-iII): 3 graded stone aggregate 20 mm nominal size) 4 x 0.50m x 0.40m x 3.00m

	shuttering, finishing and reinforcement with 1:1.5:3 (1cement: 1.5 coarse sand(zone-III): 3 graded stone aggregate 20 mm nominal size).		
	P.B: 12.70m x 0.25m x 0.30m	0.95	
	LB:12.70m x 0.25m x 0.15	0.48	
	R.B: 12.70m x 0.25m x 0.20m	0.64	
	LB: 2 x 15.0m x 0.25m x 0.15m	1.13	
	2 x 7.70m x 0.25m x 0.15m	0.58	
	M.B: 5 x 7.70m x 0.50m x 0.40m	7.70	
	R.B: 2 x 14.50m x 0.25m x 0.20m	1.45	
	2 x 7.70m x 0.25m x 0.20m	0.77	
	Roof: 14.50m x 7.70m x 0.10m	1.17	
	Chajja: 6 x 4.00m x 0.60m x 0.08m	1.15	
	2 x 1.00m x 0.60m x 0.08m	0.10	
	Stair :2 x 4.0m x 1.20m x 0.12m	1.15	
	2 x 3.00m x 1.20m x 0.12m	0.86	
		28.13	m3
7	Centering and shuttering including strutting, propping etc. and removal of form for Foundations, footings, bases of columns, etc. for mass concrete.		
	4 x 2.40m x 0.50m	4.80	
	4 x 1.80m x 2.00m	14.40	
		19.20	m2
8	Centering and shuttering including strutting, propping etc. and removal of form for:		
	Suspended floors, roofs, landings, balconies and access platform. 14.50m x 7.70m	111.65	
	6nos x 4.00m x 0.60m	14.40	
	2nos x 1.00m x 0.60m	1.20	
	2 x 4.00m x 1.20m	9.60	
	2 x 2.50m x 1.20m	6.00	
		142.85	m2
9	Centering and shuttering including strutting, propping etc. and removal of form for Lintels, beams, plinth. beams, girders, bressumers and cantilevers.		
	12.70m x 0.60m	7.62	
	12.70m x 0.30m	3.81	
	12.70m x 0.40m	5.08	
	1 47	<u> </u>	

	2 x 14.50m x 0.30m	8.70	
	2 x 7.70m x 0.30m	4.62	
	5 x 7.70m x 1.40m	53.90	
	2 x 14.50m x 0.40m	11.60	
	2 x 7.70m x 0.40m	6.16	
		101.49	m2
10	Centering and shuttering including strutting, propping etc. and removal of form for : Columns, Pillars, Piers, Abutments, Posts and Struts.		
	4 x 1.80m x 3.00m	21.60	
	10 x 1.80m x 3.00m	54.00	
		75.60	m2
11	Steel reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete above plinth level. Hot rolled deformed bars. 0.80 x 2.89=2.312		
	1.30m x 8.4 =10.92		
	1.10 x 28.13=30.943		
	44.175 qtl	4417.50	kg
12	Brick work with non modular fly ash bricks conforming to 15:12894, class designation 10 average compressive strength in super structure above plinth level up to floor V level in Cement mortar 1:4 (1 cement: 4 coarse sand).		
	12.70m x 0.30m x 0.40m	1.52	
	12.70m x 0.25m x 3.50m	10.48	
	12.70m x 0.25m x 3.00m	9.52	
	2 x 12.0m x 0.25m x 3.00m	18.00	
	2 x 7.70m x 0.25m x 3.00m	11.55	
		51.07	
	Deduction for 'D' & 'W'		
	1 x 2.00m x 3.30m x 0.25m	(-)1.65	
	6 x 3.00m x 1.50m x 0.25m	(-)6.75	
	2 x 2.10m x 1.20m x 0.25m	(-)1.26	
		41.41	m3
13	Structural steel work in single section, fixed with or without connecting plate, including cutting, hoisting. fixing in position and applying a priming coat of approved steel primer all complete.		
	(Frame: 40mm x 40mm x 6mm & 12mm Square bar)		
	15	•	•

	6nos x 3.00m x 1.50m =27.00 m2		
	01103 X 3.00111 X 1.30111 =27.00 1112		
	$2 \times 1.50 \text{m} \times 0.70 \text{m} = 2.10 \text{ m} 2$		
	29.10 m2 @25kg/m2	727.50	kg
	29.10 mz @25kg/mz	121.50	Kg
14	Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to IS: 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement: 4 coarse sand), jointing with grey cement slurry @3.3 kg/sqm including grouting the joints with white cement and matching pigments etc., complete Size of Tile 600x600 mm.		
	12.0m x 7.00m	84.50	
	38.0m x 0.10m	3.80	
	20nos x 1.20m x 0.05m	3.60	
		91.90	m2
15	Providing and laying Polished Granite stone flooring in required design and patterns, in linear as well as curvilinear portions of the building all complete as per the architectural drawings with 18 mm thick stone slab over 20 mm (average) thick base of cement mortar 1:4 (1 cement: 4 coarse sand) laid and jointed with cement slurry and pointing with white cement slurry admixed with pigment of matching shade including rubbing, curing and polishing etc. all complete as specified and as directed by the Engineer-in-charge. Polished Granite stone slab jet Black, Cherry Red, Elite Brown, Cat Eye or equivalent.		
	20 x 1.20m x 0.30m	7.20	
	3 x 1.50m x 2.50m	11.25	
		18.45	m2
16	Providing and fixing stainless steel (Grade 304) railing made of Hollow tubes, channels, plates etc., including welding, grinding, buffing, polishing and making curvature (wherever required) and fitting the same with necessary stainless steel nuts and bolts complete, i/c fixing the railing with necessary accessories & stainless steel dash fasteners, stainless steel bolts etc., of required size, on the top of the floor or the side of waist slab with suitable arrangement as per approval of Engineer-in-charge, (for payment purpose only weight of stainless steel members shall be considered excluding fixing accessories such as nuts, bolts, fasteners etc.).		
	Baluster (50 x 50)		
	$25 \text{nos } \times 0.70 \text{m} = 17.50 \text{m}$		
	Hand rail: 3 x 3.0m = 9.00m		
	26.50m @ 3.5 kg/m	92.75	kg
17	20 mm cement plaster of mix: 1:4 (1 cement: 4 fine sand)		
	7.70m x 2.50m	19.25	
	19.0m x 6.00m	114.00	
	2 x 4.00m x 1.20m	9.60	
	2 x 12.0m x 3.00m	72.00	
	2 x 7.00m x 3.00m	42.00	
	16	i .	ı

	12.00m x 7.00m	84.00	
		340.85	m2
18	20 mm cement plaster of mix: 1:4 (1 cement: 4 coarse sand)		
	12.70m x 7.00m	88.90	
	2 x 12.0m x 3.60m	86.40	
	1 x 7.70m x 3.60m	27.72	
	29.0m x 0.60m	17.40	
		220.42	m2
19	Finishing walls with Acrylic Smooth exterior paint of required shade: New work (Two or more coat applied 1.67 Itr/10 sqm over and including priming coat of exterior primer applied @ 2.20 kg/10 sqm)	220.42	m2
20	Finishing with Deluxe Multi surface paint system for Interiors and exteriors using Primer as per manufacturers specifications: Two or more coats applied on walls @ 1.25 ttr/10 sqm over and including one coat of Special primer applied @ 0.75 ltr/10 sqm.	340.85	m2
21	Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture.		
	6nos x 3.00m x 1.50m	27.00	
	2 x 1.50m x 0.75m	2.25	
		29.25	m2
22	Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid door/window/clerestory windows & clerestory other Frames/ Chowkhat comprising of virgin PVC polymer of K value 58-60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/ rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) fabricated with miter joints after applying PVC solvent cement and screwed with full body threaded star headed 55 screws having minimum frame density of 750 kg/cum, screw withdrawal strength of 2200 N (Face) & 1100 N (Edge), minimum compressive strength of 58 N/mm2, modulus of elasticity 900 N/mm2 and resistance to spread of flame of Class A category with property of being termite/borer proof, water/moisture proof and fire retardant and fixed in position with M.S hold fast/lugs/SS dash fasteners of required dia and length complete as per direction of Engineer-In-Charge. (M.S hold fast/lugs or S5 dash fasteners shall be paid for separately). Frame size 50 x 125 mm		
	1 x 5.40m	5.40	
	1 x5.70m	5.70	
		11.10	m
23	Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid plain flush door shutter of required size comprising of virgin polymer of K value 58-60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/ rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm2, modulus of elasticity 850 N/mm2 and resistance to spread of flame of Class A category with property of being termite/borer proof, water/moisture proof and fire retardant and foxing with stainless steel butt hinges of required size with necessary full body threaded star headed counter sunk S.S screws, all as per direction of Engineer-In-Charge. (Note: stainless steel butt hinges and necessary S.S		

	screws shall be paid separately)35 mm thick.		
	2.10m x 1.20m	2.52	
	2.10m x 1.50m	3.15	
		5.67	m2
24	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing/paneling, C.P.brass/stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in- charge. (Glazing, paneling and dash fasteners to be paid for separately):For fixed portion Powder coated aluminium (minimum thickness of powder coating 50 micron) 6 x 3.00m x 1.50m = 27.00 m2		
	2 x 1.50m x 0.70m = 2.10 m2		
	29.10m2 @6.00kg/m2	174.60	kg
25	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing/paneling. C.P.brass/stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in- charge. (Glazing, paneling and dash fasteners to be paid for separately): For shutters of doors, windows & ventilators including providing and fixing hinges/pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber/neoprene gasket required (Fittings shall be paid for separately) Powder coated aluminium (minimum thickness of powder		
	coating 50 micron) 6 x 3.00m x 1.50m =27.00m2@5.5kg/m2	148.50	kg
26	coating 50 micron)	27.00 2.10	kg
26	coating 50 micron) 6 x 3.00m x 1.50m =27.00m2@5.5kg/m2 Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber/ neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge. (Cost of aluminium snap beading shall be paid in basic item): With float glass panes of 5 mm thickness (weight not less than 12.50 kg/sqm) 6 x 3.00m x 1.50m	27.00	kg m2
26	coating 50 micron) 6 x 3.00m x 1.50m =27.00m2@5.5kg/m2 Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber/ neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge. (Cost of aluminium snap beading shall be paid in basic item): With float glass panes of 5 mm thickness (weight not less than 12.50 kg/sqm) 6 x 3.00m x 1.50m	27.00	
27	coating 50 micron) 6 x 3.00m x 1.50m =27.00m2@5.5kg/m2 Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber/ neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge. (Cost of aluminium snap beading shall be paid in basic item): With float glass panes of 5 mm thickness (weight not less than 12.50 kg/sqm) 6 x 3.00m x 1.50m 2 x 1.50m x 0.70m Grading roof for water proofing treatment with Cement concrete 1:2:4 (1 cement: 2 coarse sand: 4 graded stone aggregate 20mm nominal size) 14.50m x 7.20m x 0.08 Removing mortar from bricks and cleaning bricks including stacking within a lead of 50 m	27.00 2.10 29.10	m2
	coating 50 micron) 6 x 3.00m x 1.50m =27.00m2@5.5kg/m2 Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber/ neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge. (Cost of aluminium snap beading shall be paid in basic item): With float glass panes of 5 mm thickness (weight not less than 12.50 kg/sqm) 6 x 3.00m x 1.50m 2 x 1.50m x 0.70m Grading roof for water proofing treatment with Cement concrete 1:2:4 (1 cement: 2 coarse sand: 4 graded stone aggregate 20mm nominal size) 14.50m x 7.20m x 0.08	27.00 2.10 29.10	m2

		5.25	m3
29	29 Demolishing R.C.C. work manually/ by mechanical means Including stacking of steel bars and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge		
	8x0.50m x 0.40m x 0.70m	1.12	m3
30	Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer In charge. Nominal concrete 1:4:8 or leaner mix (i/c equivalent design mix).		
	12.0m x 7.0m x 0.08m	6.72	m3
	ELECTRICAL INSTALLATION		
31	Supplying and fixing of following ways surface/ recess(4+12)mounting, vertical type, 415 V, TPN MCB distribution board of sheet steel, dust protected, duly powder painted, inclusive of 200 A tinned copper bus bar, common neutral link, earth bar, din bar for mounting MCBs (but without MCBs and incomer) as required. (Note: Vertical type MCB TPDB is normally used where 3 phase outlets are required.)	1.00	set
32	Wiring for circuit/submain wiring along with earth wire with the following sizes(4 X 10 sq. mm + 2 X 6 sq. mm earth wire) of FRLS PVC insulated copper conductor, single core cable in surface/ recessed medium class PVC conduit as required.	20.00	mt
33	Wiring for circuit/submain wiring along with earth wire with the following sizes(2 X 4 sq. mm + 1 X 4 sq. mm earth wire) of FRLS PVC insulated copper conductor, single core cable in surface/ recessed medium class PVC conduit as required.	68.00	mt
34	Wiring for circuit/submain wiring alongwith earth wire with the following sizes (2 X 2.5 sq. mm + 1 X 2.5 sq. mm earth wire) of FRLS PVC insulated copper conductor, single core cable in surface/recessed medium class PVC conduit as required.	60.00	mt
35	Supplying and fixing suitable size Gl box with modular plate and cover in front on surface or in recess, including providing and fixing 1 no. 5 pin 15/16 A modular socket outlet and 1 no.25A modular AC starter, connections etc	4.00	Nos
36	Supplying and fixing of 63A 4pole MCB as required.	1.00	no
37	Wiring for light point/fan point/ exhaust fan point/call bell point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable in surface/recessed PVC conduit, with modular switch, modular plate, suitable GI box and earthing the point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable etc. as required.	18.00	point
38	Supplying and fixing suitable size GI box with modular plate and cover in front on surface or in recess, including providing and fixing 3 nos. 5 pin 5/6 A modular socket outlet and 3 nos. 5/6 A modular switch, connections etc. as required	4.00	nos
39	Supplying and fixing of 22W LED surface panel light(Sqare type) as required.	10.00	nos
40	Supplying and fixing of 26W high speed BLDC ceiling fan(48") with good star rating as required.	8.00	nos
41	Supplying and fixing of modular regulator as required.	8.00	nos
42	Supplying and fixing of 32A C type SP MCB as required.	4.00	nos
43	Supplying and fixing of 25A C type SP MCB as required.	4.00	nos
44	Supplying and fixing of 16A C type SP MCB as required.	2.00	nos
45	Earthing with G.I. earth pipe 4.5 metre long, 40 mm dia including Gl wire accessories, and providing masonry enclosure with over plate having locking arrangement and watering pipe etc. with charcoal/coke and salt as required.	1.00	no
46	Supplying and fixing of light class G.I. pipe of 75mm dia. (nominal) 3 metres length along the pole for protection of under ground cable as required.	1.00	no