

ಭಾ. ಕೃ. ಅನು. ಪ – ಭಾರತೀಯ ತೋಟಗಾಲಿಕಾ ಸಂಶೋಧನಾ ಸಂಸ್ಥೆ ಹೆಸರಫಟ್ಟ ಕೆರೆ ಅಂಜೆ, ಖೆಂಗಟೂರು–560 089 भा.कृ.अनू.प.– भारतीय बागवानी अनूसंधान संस्थान हेसरघट्टा लेक पोस्ट, बेंगलूरू – 560 089 **ICAR-Indian Institute of Horticultural Research** Hesaraghatta Lake Post, Bengaluru - 560 089 EPABX: 080-23086100 Extn: 218 & 217

FAX: 080-28466291 – Email: purchase.iihr@icar.gov.in

F.No.5-90/2023-24/SP/IIHR/

Dated:14.12.2023

#### NOTICE FOR INVITING TENDER THROUGH E-PROCUREMENT

Online Bids are invited from interested firms under Two bid system (Technical bid/financial bid) for Construction extension to ABI incubation facility 09mt x 05mt (Sheet roof structure) ICAR-IIHR H'ghatt, Bangalore. Manual bids will not be entertained.

Tender documents may be downloaded from e-procurement website of CPPP https://eprocure.gov.in/eprocure/app as per the schedule given in CRITICAL DATE SHEET as under:

Tender No.	F.No.5-90/2023-24/SP/IIHR/
	ICAR-INDIAN INSTITUTE OF
Name of Organization	HORTICULTURAL RESEARCH,
	Hessaraghatta Lake Post, Bangalore
Date and Time for Issue/Publishing	14.12.2023 at 05:00 PM
Document Download/Sale Start Date	14.12.2023 at 05:00 PM
and Time	
Bid Submission start Date and Time	14.12.2023 at 05:00 PM
Bid Submission End Date and Time	02.01.2024 at 03:00 PM
Date and Time for Opening of Technical Bids	04.01.2024 at 10:00 AM
Address for Communication	Senior Administrative Officer (Purchase), IIHR,
	Hessaraghatta Lake Post, Bangalore

#### **CRITICAL DATE SHEET**

#### Sd/-**CHIEF ADMINISTRATIVE OFFICER**

#### Annexure-I

#### **INSTRUCTIONS FOR ONLINE BID SUBMISSION**

- The Tender form/bidder documents may be downloaded from the <u>https://eprocure.gov.in/eprocure/app.</u> Online submission of Bids through Central Public Procurement Portal (<u>https://eprocure.gov.in/eprocure/app</u>) is mandatory. Manual/Offline bids shall not be accepted under any circumstances.
- 2. Tenderers/bidders are requested to visit the website <u>https://eprocure.gov.in/eprocure/app</u> regularly. Any changes/modifications in tender enquiry will be intimated by corrigendum through this website only.
- 3. In case, any holiday is declared by the Government on the day of opening, the tenders will be opened on the next working day at the same time. The Council reserves the right to accept or reject any or all the tenders.
- 4. The Firms are required to deposit (in original) EMD of Rs.29,000 /- in the shape of Demand Draft in favour of THE DIRECTOR, ICAR, UNIT-IIHR payable at Bangalore may be address to Senior Administrative Officer (Purchase), IIHR, Hesaraghatta Lake Post, Bangalore-560089 on or before bid opening date and time as mentioned in the Critical Date Sheet.

#### 5. Please note that only online Bids will be accepted.

- 6. Bidders need not to come at the time of Technical as well as Financial bid opening at IIHR. They can view live bid opening after login on CPPP e-procurement portal at their remote end. If any dispute arises, Within Bengaluru Jurisdiction only.
- 7. The firms are also required to upload copies of the following documents for Technical eligibility and Evaluation:-

#### • Technical Bid

- 1. Scanned copy of the documents Registered with PWD/CPWD/MES/Railways.
- 2. PAN Card copy
- 3. GST Number with Registration Certificate
- 4. Bank details of the firm.
- 5. Scanned copy of Income Tax Returns statement for Financial Year 2019-20, 2020-21, 2021-22
- 6. Scanned copy of Profit and loss account & Balance Sheet which are audited & duly certified by the Chartered Accountant for Financial Year <u>2019-20</u>, <u>2020-21</u>, <u>2021-22</u>.
- 7. Turnover of the business should be <u>Rs45.00 Lakhs</u> per year (2019-20, 2020-21, 2021-22), and Chartered Accountant certified profit or Loss Account ; Balance Sheets to this effect may be enclosed.
- 8. Scanned copy of work/supply order for having successfully completed similar works during last <u>5 years</u> ending last day of month previous to the one in which bids are invited should be

either of the following:

- a) Three similar completed works costing not less than Rs5,71,000/- each
- b) Two similar completed works costing not less than Rs.7,13,000/- each
- c) One similar completed work costing not less than Rs.11,42,000/- each

(similar work: stone missionary foundation, RCC plinth Bleam, solid block missionary wall, aluminum windows ,vitrified floor tiles, steel work fabrication, roof pre - coated steel work, self driven fans, false cealing)

#### 9. <u>Exemption of EMD is not provided for MSME or Udyog Aadhar or NSIC Registration</u> <u>firms and other firms.</u>

- 10. Signed and scanned copy of Tender acceptance letter (Annexure-V) is mandatory.
- 11. Latest copies of the GST returns for 6 month(January to June, 2023) is to be attached

#### • Financial Bid:-

- a) Price Bid as BOQ XXX.xls
- b) The estimates is based on latest CPWD-DSR with all updates and correction slips. Firms/Contractors/Bidders should not quote too low or too high. To ensure quality materials, specification and workmanship, any tender with more than (+) or (-) 15% variation over and above or below the basic estimated cost will be summarily rejected.
- c) So, the bidders must take due care while quoting.
- d) Evaluation criteria: Tender will be awarded to the lowest quoted Firm among those firms qualified in the Technical Bid. In case, two or more firms quote the same amount in r/o all the items work together as a whole, then the tender will be awarded to the Firm which has got more average turnover in the last 3 years, based on IT returns/Profit & Loss account/Turnover duly certified by the CA and uploaded along with Tender through CPP.

Sd/-CHIEF ADMINISTRATIVE OFFICER

#### Annexure-II

#### **Terms & Conditions**

- 1. The tenderer shall quote rates, which will include the supply, installation & other incidental charges.GST, if any, should be indicated separately.
- 2. The rates should be quoted as per the BOQ uploaded on the CPP Portal (reference may be obtained from Annexure-III). GST, if any, should be indicated separately. It must be noted that the contract shall be awarded to the firm which fulfils all the required terms and conditions and remains L-I for Total cost.
- 3. The firm must also possess valid PAN No. & GST registration number and a copy of the same must also be enclosed with the tender document.
- 4. Scanned copy of Income Tax Returns statement for Financial Year 2019-20, 2020-21, 2021-22.
- 5. Turnover of the business should be Rs.45.00 Lakhs per year (2019-20, 2020-21, 2021-22), and Chartered Accountant certified profit or Loss Account ; Balance Sheets to this effect may be enclosed.
- 6. Exemption of EMD is not provided for MSME or Udyog Aadhar or NSIC Registration <u>firms and other firms.</u>
  T. Latest copies of the GST returns for 6 month(January to June,2023) is to be attached
- 8. Modification in the tender documents after the closing date is not permissible.
- 9. The successful firm shall commence work within 10 days from the date of confirmed work order and if the work not completed in time then EMD shall be forfeited. The rates quoted shall be valid for one year from the date of opening of tender.
- 10. The contractor/bidder or his representative may contact the undersigned at Tel. No. 080-23086100 Extn: 217 & 211 for any further clarification. No variation in terms and quality of the items/specifications shall be entertained or else EMD/Security deposit shall be forfeited.
- 11. The bidder is advised to visit the site of works at his own expenses and obtain all information that may be necessary for preparing the quotation. Submission of quotation is acceptance by the tenderer that he has inspected the site or he is aware of all conditions.
- 12. The Director, ICAR-IIHR, shall have the right to reject all or any of the offers, accept more than one offer, and assign part of the job without assigning any reason.
- 13. Merely quoting of lowest rates does not mean that order shall be given to that firm. The competent authority will finally decide on the basis of quality & performance of past installations.
- 14. The Firms are required to deposit (in original) an Earnest Money Deposit of Rs.29,000/amount mentioned against item in the form of Demand Draft from any of the Commercial Bank in favour of THE DIRECTOR, ICAR, UNIT-IIHR payable at Bangalore may be address to Senior Administrative Officer (Purchase), IIHR, Hessaraghatta Lake Post, Bangalore-560089 on or before bid opening date and time as mentioned in the Critical Date Sheet. No quotation shall be considered without the earnest money deposit. Demand draft drawn in favour of any officer other than 'THE DIRECTOR, ICAR UNIT-IIHR payable at Bangalore' will not be accepted and the tender will be rejected. The earnest money will be refunded only after the finalization of the procurement and no interest will be paid on earnest

money. The request letter for refund of EMD & performance security is to be submitted by the firm.

- 15. Rates once finalized will not be enhanced/reduced during the currency of the contract.
- 16. In case, the successful bidder shows inability at any stage, after the contract is finalized and awarded, for whatsoever reason(s), to honour the contract, the earnest money /performance security deposited would be forfeited.
- 17. The Director, ICAR-IIHR reserves the right to cancel the contract at any time during the currency period of the contract without giving any reason.
- 18. The firm, to whom the tender will be awarded, will have to deposit the performance security equal to 3% of the total quoted amount at which the Tender will be awarded within 21 days from the date of receipt of work order and the same will be retained during the Defect liability period(warranty) of One year. In the sense, for any material and execution defects, the firm has to set right the defects within 10 working days and maintain the said work. If the services are not found to be satisfactory, the performance security is liable to be forfeited. No interest will be paid on performance security.
- 19. If any dispute(s) arises between IIHR and the firm with reference to the contract, IIHR will decide it and its decision will be binding on the firms.
- 20. Bid Validity: 90 days
- 21. Payment:- No advance or part payment will be given. The payment will be released after satisfactory completion of the work and certificate from the Indentor/Engineer.
- 22. The supplier/firm has to submit the GST return for having remitted the GST amount paid by the institute to the concerned authority within 30 days from receipt of payment from IIHR, otherwise their EMD and SD/PS will not be released and such firms shall be blocklisted.
- 23. GST extra as applicable should be indicated separately in the column provided. Otherwise such quotes will be rejected.

Payment Terms: In order to facilitate for speedy settlement of payment you are requested to furnish the following details as below:

- 1. Name of the firm:
- 2. Name of the Bank:
- 3. IFSC Code of Bank:
- 4. Name of the Account & Account No.:
- 5. Branch Code:
- 6. Amount to be paid:
- 7. E-mail address of the party:
- 8. GST No. and Pan No. Copies

'Terms & Conditions are acceptable'

Dated

(Authorized signatory of the firm)

Annexure-III

(Reference for BOQ) (To be quoted in format provided on CPP Portal)

# Price bid for: Construction extension to ABI incubation facility 09mt x 05mt (Sheet roof structure) ICAR-IIHR H'ghatt, Bangalore.

Sl. No.	Name of item	Quantity	Per unit price* (in figures/words) (as per BOQ)
01	Construction extension to ABI incubation facility 09mt x 05mt (Sheet roof structure) ICAR-IIHR H'ghatt, Bangalore	01 Unit	

\*Annexure-VIII

- Items should be of reputed make and suitable for high end elite users
- GST extra as applicable should be indicated separately in the column provided. Otherwise such quotes will be rejected.
- ICAR-IIHR Bangalore.

**Note:** The above mentioned Financial Proposal/Commercial bid format is provided as BoQ\_XXXX/xls along with this tender document at <u>https://eprocure.gov.in/eprocure/app.</u> Bidders are advised to download this BoQ\_XXXX.xls as it is and quote their offer/rates in the permitted column and upload the same in the Financial bid. **Bidder shall not tamper/modify downloaded price bid template in any manner**. In case if the same is found to be tempered/modified in any manner, tender will be completely rejected and EMD would be forfeited and tenderer is liable to be banned from doing business with IIHR.

#### Annexure-IV

EPABX: 080-23086100 Extn: 218 & 217 FAX: 080-28466291 - Email: purchase.iihr@icar.gov.in



# ICAR-INDIAN INSTITUTE OF HORTICULTURAL RESEARCH

HESSARAGHATTA LAKE POST, BANGALORE-560 089

Name of the Firm\_\_\_\_\_

Registered/Postal Address\_\_\_\_\_

1	Permanent Account Number (PAN)	
2	GST Registration No.	
3	Bank Details	
a	Bank Name	
b	Branch Address	
с	Account Number	
d	Type of account (current/saving) MICR No.	
e	IFSC Code	

Date:

Name of the Authorized Signatory

Place:

Stamp & Signature

## Annexure-V TENDER ACCEPTANCE LETTER

(To be given on Company Letter Head)

#### Date:

To,

The Director, ICAR-IIHR, Hesaraghatta Lake Post, Bangalore-560089.

Sub: Acceptance of Terms & Conditions of Tender.

Tender Reference No.\_\_\_\_\_

Name of Tender/Work:

Dear Sir,

1. I/ We have downloaded/obtained the tender document(s) for the above mentioned' Tender/work' from the web site(s) namely:

As per your advertisement, given in the above mentioned website(s).

2. I/We hereby certify that I/We have read the entire terms and conditions of the tender documents from Page No. \_\_\_\_\_\_to \_\_\_\_\_(including all documents lime annexure(s), schedule(s), etc...) which form part of the contract agreement and I/We shall abide hereby the terms/conditions/clauses contained therein.

3. The corrigendum(s) issued from time to time by your department/organization too have also been taken into consideration, while submitting this acceptance letter.

4. I/we hereby unconditionally accept the tender conditions of above mentioned tender documents/corrigendum(s) in its totality/entirely.

5. I/we do hereby declare that our Firm has not been black-listed/debarred by any Govt. Department/Public sector undertaking.

6. I/we certify that all information furnished by our Firm is true & correct and in the event that the information is found to be incorrect/untrue or found violated, then your department/organization shall without giving any notice or reason therefore or summarily reject that bid or terminate the contract, without prejudice to any other rights or remedy including the forfeiture of the full said earnest money deposit absolutely.

Yours Faithfully,

(Signature of the Bidder, with Official Seal)

#### Annexure-VI

#### **INSTRUCTIONS FOR ONLINE BID SUBMISSION**

The bidders are required to submit soft copies of their bids electronically on the CPP Portal, using valid Digital Signature Certificates. The instructions given below are meant to assist the bidders in registering on the CPP Portal, prepare their bids in accordance with the requirements and submitting their bids online on the CPP Portal.

More information useful for submitting online bids on the CPP Portal may be obtained at <u>https://eprocure.gov.in/eprocure/app</u>.

#### REGISTRATION

• Bidders are required to enroll on the e-Procurement module of the Central Public Procurement Portal (URL <u>https://eprocure.gov.in/eprocure/app</u>.) by clicking on the link '**Online bidder Enrollment'** on the CPP Portal which is free of charge.

• As part of the enrolment process, the bidders will be required to choose a unique username and assign a password for their accounts.

• Bidders are advised to register their valid email address and mobile numbers as part of the registration process. These would be used for any communication from the CPP Portal.

• Upon enrolment, the bidders will be required to register their valid Digital Signature Certificate (class II or Class III certificates with signing key usage) issued by any certifying authority recognized by CCA India (e.g. Sify/nCode/eMudhra etc.) with their profile.

• Only one valid DSC should be registered by a bidder. Please note that the bidders are responsible to ensure that they do not lend their DSC's to others which may lead to misuse.

• Bidder then logs in to the site through the secured log-in by entering their users ID/password and the password of the DSC/e-Token.

#### SEARCHING FOR TENDER DOCUMENTS

• There are various search options built in the CPP Portal. To facilitate bidders to search active tenders by several parameters. These parameters could include Tender ID, Organization Name, Location, Date, Value etc. There is also an option of advanced search for tenders, wherein the bidders may combine a number of search parameters such as Organization Name, Form of Contract, Location, Date, Other keywords etc. to search for a tender published on the CPP Portal.

• Once the bidders have selected the tenders they are interested in, they may download the required documents/tender schedules. These tenders can be moved to the respective 'My Tenders' folder. This would enable the CPP Portal to intimate the bidders through SMS/e-mail in case there is any corrigendum issued to the tender document.

• The bidder should make a note of the unique Tender ID assigned to each tender, in case they want to obtain any clarification/help from the Helpdesk.

#### **PREPARATION OF BIDS**

• Bidder are requested to visit the site at the institute and discuss with ACTO(Works), ICAR-IIHR, Bangalore before preparing the bid clarify the doubts and understand the requirements.

• Bidder should take into account any corrigendum published on the tender document before submitting their bids.

• Please go through the tender advertisement and the tender document carefully to understand the documents required to be submitted as part of the bid. Please note the number of covers in which the bid documents have to be submitted, the number of documents- including the names and content of each of the document that need to be submitted. Any deviations from these may lead to rejection of the bid.

• Bidder, in advance, should get ready the bid documents to be submitted as indicated in the tender document/schedule and generally, they can be in PDF/XLS/RAR/DWF/JPG formats. Bid documents may be scanned with 100 dpi with black and white option which helps in reducing size of the scanned document.

• To avoid the time and effort required I uploading the same set of standard documents which are required to be submitted as a part of every bid, a provision of uploading such standard documents (e.g. PAN card copy, annual reports, auditor certificates etc.) has been provided to the bidders. Bidders can use 'My Space' or 'Other important Documents' area available to them to upload such documents. These documents may be directly submitted from the 'My Space' area while submitting a bid, and need not be uploaded again and again. This will lead to a reduction in the time required for bid submission process.

#### SUBMISSION OF BIDS

•

• Bidder should log into the site will in advance for bid submission so that they can upload the bid in time i.e. on or before the bid submission time. Bidder will be responsible for any delay due to other technical issues.

• The bidder has to digitally sign and upload the required bid documents one by one as indicated in the tender document.

• Bidder has to select the payment option as 'offline' to pay the tender fee/EMD as applicable and enter details of the instrument.

• Bidder should prepare the EMD as per the instructions specified in the tender document. The original should be posted/couriered/given in person to the concerned official, latest by the last date of bid submission or as specified in the tender documents. The details of the DD/any other accepted instrument, physically sent, should tally with the details available in the scanned copy and the data entered during bid submission time. Otherwise the uploaded bid will be rejected.

• Bidders are requested to note that they should necessarily submit their financial bids in the Format provided and no other format is acceptable. If the price bid has been given as a standard BoQ format with the tender document, then the same is to be downloaded and to be filled by all the bidders. Bidders are required to download the BoQ file, open it and complete the white coloured (unprotected) cell with their respective financial quotes and other details (such as name of the bidder). No other cells should be changed. Once the details have been completed, the bidder should save it and submit it online, without changing the filename. If the BoQ file is found to be modified by the bidder, the bid will be rejected.

• The server time (which is displayed on the bidders' dashboard) will be considered as the standard time for referencing the deadlines for submission of the bids by the bidders, opening of bids etc. The bidders should follow this time during bid submission.

• All the documents being submitted by the bidders would be encrypted using PKI encryption techniques to ensure the secrecy of the data. The data entered cannot be viewed by unauthorized persons until the time of bid opening. The confidentiality of the bids is maintained using the secured Socket Layer 128 bit encryption technology. Data storage encryption of sensitive fields is done. Any bid document that is uploaded to the server is subjected to symmetric, encryption using a system generated symmetric key. Further this key is subjected to asymmetric encryption using buyers/bid openers public keys. Overall, the uploaded tender documents become readable only after the tender opening by the authorized bid openers.

• The uploaded tender documents become readable only after the tender opening by the authorized bid openers.

• Upon the successful and timely submission of bids (i.e. after clicking 'Freeze Bid Submission' in the portal), the portal will give a successful bid submission message and a bid summary

will be displayed with the bid no. and the date and time of submission of the bid with all other relevant details.

• The bid summary has to printed and kept as an acknowledgement of the submission of the bid.

#### **ASSISSTANCE TO BIDDERS**

• Any queries relating to the tender documents and the terms and conditions contained therein should be addressed to the Tender Inviting Authority for a tender or the relevant contract person indicated in the tender.

• Any queries relating to the process of online bid submission or queries relating to CPP Portal in general may be directed to the 24x7 CPP Portal Helpdesk.

\*\*\*\*

#### Annexure-VII

Details of Works & EMD

S1.	Purchase of item	Qty	Earnest	File. No. for reference
			Money in	
No.			INR	
	Construction extension to ABI incubation			
	facility 09mt x 05mt (Sheet roof structure)			
	ICAR-IIHR H'ghatt, Bangalore	01		
01		UNIT	Rs.29,000/-	F.No.5-90/2023-24/SP/IIHR

Note: EMD defined on to the Portal is MINIMUM. Bidder has to submit the EMD as per item for which quoting for.

#### \* ICAR-IIHR Bangalore.

# \*\* Exemption of EMD is not provided for MSME or Udyog Aadhar or NSIC Registration firms and other firms.

#### Annexure-VIII

### TECHNICAL SPECIFICATION FOR CONSTRUCTION EXTENSION TO ABI INCUBATION FACILITY 09MT X 05MT (SHEET ROOF STRUCTURE) ICAR-IIHR <u>H'GHATT, BANGALORE</u>

No	Details Civil works–I	Unit	Qty
1	Earth work in excavation by mechanical means(Hydraulicexcavator)/manual means over areas (exceeding30cmindepth,1.5minwidthaswellas10 sqm on plan) including getting out and disposalofexcavatedearthleadupto50mandliftupto1.5m,as directed by Engineer-in- charge. All kinds of soil For wall foundation	Cum	16
2	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level : 1:5:10 (1 cement : 5coarse sand (zone- III)derivedfromnaturalsources:10gradedstoneaggregate40mmnominal sizederivedfrom natural sources) for wall foundation, flooring and plinth protection, column footing base	Cum	10
3	Randomrubblemasonrywithhardstoneinfoundationandplinthincludinglevell ingupwithcement concrete1:6:12(1cement:6coarsesand:12gradedstoneaggregate20mm nominalsize)upto plinth level with Cement mortar 1:6 (1 cement : 6 coarses and)	Cum	14
4	Centering and shuttering including strutting, propping etc. and removal of form for For chajja For lintel plinth beam Drain slab	Sqm Sqm Sqm Sqm	16 23 11 08
5	Steel reinforcement for R.C.C. work including straightening, cutting,bending, placing in positionandbindingallcompleteuptoplinthleveland above plinth level, Thermo-Mechanically Treated bars of grade Fe-500D or more, lintel, chajja, For plinth beam, drain slab	Kg Kg	350 400
6	Providingandconstructingconcreteblockmasonryusing150x200x400m msolidcorecompact concreteblock(GradeC- 50Kg/Cm <sup>2</sup> )inCM1:6includingallscaffolding,curing,etc.complete Forwalls	Sqm	95

7	Providing and laying in position specified grade of reinforced	Cum	04
	cementconcrete, excluding the cost of centering, shuttering, finishing		
	and reinforcement-Allworkuptoplinthlevel 1:2:4(1		
	cement:2coarsesand(zone-		
	III)derivedfromnaturalsources:4gradedstoneaggregate20mm nominal		
	size derivedfromnaturalsources) for plinth beam		

8	Reinforcedcementconcreteworkinlintelbeams, chajjaaboveplinthlevelup		
	tofloorfivelevel, excludingthecostofcentering, shuttering, finishing and		
	reinforcement with 1:1.5:3(1 cement :		
	1.5coarsesand(zone-		
	III)derivedfromnaturalsources:3gradedstoneaggregate20mmnominal	Cum	04
	size derived from natural sources)		
	Forlintelandchajja,allroundbeamatrooflevel		
	Providing and fixing precoated galvanised steel sheet roofing		
	accessories 0.50 mm + 0.05 %		
	totalcoatedthickness,Zinccoating120gsmasper IS:277in240mpasteel		
	grade, 5-7 microns epoxybothsideofthesheetandpolyestertopcoat15-	Sqm	60
	18micronsusingselfdrilling/selftapping	oqm	00
	screwscompletetiledshapedasperapprovedsample Forroof,		
	ridge		
	ProvidingCementplaster1:3(1cement:3coarsesand)fi		
	nishedwithafloating coat of neat cement. 12 mm	Sqm	350
	cement plaster	Oqm	000
	Providingandapplyingwhitecementbasedputtyofaveragethickness1m	Sqm	135
	m,ofapproved brand and manufacturer, over the plastered wall	Oqm	100
	surface to prepare the surface even and smooth complete. (Asian		
	Tractor / Jonson Nicholson / Berger)	Sqm	205
	Applyingonecoatofwaterthinnablecementprimerofapprovedbrandand	Sqiii	205
	manufactureon wall surface Water thinnable cement primer	Sam	105
	Wall painting with acrylic emulsion paint, having VOC (Volatile	Sqm	135
	Organic Compound) content less than 50 grams/ litre, of approved		
	brand and manufacture, including applying additional coats wherever		
	required, to achieve even shade and colour. Two coats		
	(AsianTractor/JonsonNicholson /Berger)	0	
	Finishing walls with AcrylicSmooth exteriorpaint ofrequired shade New	Sqm	70
	work (Twoormore		
	coatapplied@1.67ltr/10sqmoverandincludingprimingcoatofexteriorprim		
	erapplied@		
	2.20kg/10sqm)(AsianTractor/Jonson Nicholson/Berger)		
	Steelworkinbuiltuptubular(round,squareorrectangularhollowtubesetc.)tru		
	ssesetc.,including cutting, hoisting, fixing in position and		• <b>-</b> -
	applyingaprimingcoatofapprovedsteelprimer,etc. complete.Angles	Kgs	975
	and 10 mm solid rod forwindow grill , roof truss		
	Painting with synthetic enamel paint of approved brand	Sqm	50
	andmanufactureofrequiredcolourto giveanevenshade Two or more		
	coats on new work over an under coat ofsuitableshadewith		
	ordinarypaintofapprovedbrandandmanufacture . (Asian Tractor /		
	Jonson Nicholson / Berger)		

17	Providing and fixing pressed steel door frames conforming to IS: 4351,manufactured from commercialmildsteelsheetof1.60mmthickness,includinghinges,jamb,loc kjamb,beadandif required angle threshold of mild steel angle of section 50x25 mm, or base ties of 1.60 mm, pressedmildsteelweldedorrigidlyfixedtogetherbymechanicalmeans,includ ingM.S.pressedbutt hinges2.5mmthickwithmortarguards,lockstrike- plateandshockabsorbersasspecifiedand applyingacoatofapprovedsteelprimerafterpre- treatmentofthesurfaceasdirectedbyEngineer- in-charge Fixing with adjustable lugs with split end tail to eachjamb	Rmt	5.4
18	ProvidingandfixingISImarkedflushdoorshuttersconformingtoIS2202(P artI)non-decorative type,coreofblockboardconstructionwith frame of 1st class hard wood and well matched commercial3plyveneeringwithverticalgrainsorcrossbandsandfacevene ersonbothfacesof shutters30mmthickincludingISImarkedStainlessSteelbutthingeswithne cessaryscrews	Sqm	2.52
19	Providingandfixingbrightfinishedbrasshangingtypefloordoorstopper with necessary screws, etc. complete	Sqm	02
20	Providing and fixing bright finished brass tower bolts (barrel type) withnecessary screws etc. complete 150x10 mm	Each	04
21	Providingandfixingbrightfinishedbrassdoorlatchwithnecessaryscrewse tc.complete250x16x5 mm	Each	04
22	Providingandfixingaluminiumhandles,ISImarked,anodised(anodiccoati ngnotlessthangrade AC10asperIS:1868)transparentordyedtorequiredcolourorshade,withn ecessaryscrewsetc. complete125mm	Each	04
23	Providing and fixing top self driven rotating exhaust fans 2 feet sizes with necessary and providing additional support to hold the fans at required said position complete as required at site and directed by the Engineer at site and as per approved sample of the fan	Nos	04
24	Bankingexcavatedearthinlayersnotexceeding20cmindepth,breakingcl ods,watering,rolling eachlayerwith½tonneroller,orwoodenorsteelrammers,androllingevery 3rdandtop-most layer withpowerrollerofminimum8tonnesanddressingup,inembankmentsforr oads,flood banks,marginalbanks,andguidebanksetc.,leadupto50mand lift upto 1.5 m all kinds of soil	Cum	27
25	Filling available excavated earth (excluding rock) in trenches, plinth, sides of foundations etc. in layers not exceeding 20cm in depth, consolidating each deposited layer by ramming and watering,leadup to 50 m and lift upto 1.5 m.	Cum	10

	Providing and laying vitrified floor tiles in different sizes (thickness to bespecified by the manufacturer) with water absorption less than 0.08%andconformingtoIS:15622,ofapproved make,inallcoloursandshades,laidon20mmthickcementmortar1:4(1cem ent:4coarsesand), jointingwithgreycementslurry@3.3kg/sqmincludinggroutingthejointswit hwhitecement and matching pigments etc., complete SizeofTile600x600mm	Sqm	47
27	Providingandfixingaluminiumworkfordoors,windows and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conformingtoIS:733andIS:1285,fixingwithdashfastenersofrequireddiaa ndsize,including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/neoprenegasketetc.Aluminiumsectionsshallbesmooth,rustfree, straight,mitredand	Kg	45
	jointedmechanicallywhereverrequiredincludingcleatangle,Aluminiums napbeadingforglazing /paneling,C.P. brass /stainless steel screws,all completeas perarchitectural drawingsandthe directionsofEngineer-in- charge.(Glazing,panelinganddashfastenerstobepaidforseparately) Powder coated aluminium (minimum thicknessofpowdercoating50micron)		
28	For shutters of doors, windows & ventilators includingprovidingandfixinghinges/pivotsand making provisionfor fixing of fittings wherever required including the costof EPDM rubber / neoprene gasket required (Fittings shall be paid for separately) Powder coated aluminium (minimum thickness of powder coating 50 micron)	Kg	50
29	Providing and fixing glazing in aluminium door, window, shutters and partitions etc. with EPDM rubber / neoprene gasket etc.completeasperthearchitecturaldrawingsandthe directionsofengineer-in- charge.(Costofaluminiumsnapbeadingshallbepaidin basic item): Withfloatglasspanesof4.0mmthickness(weightnot less than 10kg/sqm) plain glass	Sqm	06
30	Supplyingandfixingwithclose nitSSmeshasper approvedsampleforaluminium shutters	Sqm	03
31	Providing and fixing tiled false ceiling of specified materials of size 595x595 mm in true horizontallevel,suspendedoninterlockingmetalgridofhotdippedgalvaniz edsteelsections( galvanized@120grams/sqm,bothsideinclusive)consistingofmain"T"run nerwithsuitably spacedjointstogetrequiredlengthandofsize24x38mmmadefrom0.30m mthick(minimum) sheet, spaced at 1200 mm center to center and cross "T" of size 24x25 mm made of 0.30 mm thick(minimum)sheet,1200mmlongspacedbetweenmain"T"at600mmc entertocenterto form a grid of 1200x600 mm and secondary cross "T"	Sqm	45

	of length 600 mm and size 24x25 mm madeof0.30mmthick(minimum)sheettobeinterlockedatmiddleofthe120 0x600mmpanel toformgridsof600x600mmandwallangleofsize24x24x0.3mmandlayingf alseceilingtiles of approved texture in the grid including, required cutting/making, opening for services like diffusers, grills, light fittings, fixtures, smoke detectors etc. Main "T" runners to be suspended fromceilingusingGIslottedcleatsofsize27x37x25x1.6mmfixedtoceilingw ith12.5mm dia and 50 mm long dash fasteners, 4 mm GI adjustable rods with galvanised butterfly level clipsofsize85x30x0.8mmspacedat1200mmcentertocenteralongmainT, bottomexposed width of 24 mm of all T-sections shall be pre-painted with polyester paint, all complete for all heights as per specifications, drawings and as directed by Engineer-in-charge. 12.5 mm thick square edge PVC Laminated Gypsum Tile of size 595x595 mm, made of Gypsumplasterboard,manufacturedfromnaturalgypsumasperIS2095p		
	artlandlaminated with white 0.16mm thick fire retardant PVC film on the face side and 12micron metalized		
	polyesteronthebacksidewithalledgessealedwith		
	SUBHEAD:12.0ROOFING266Code DescriptionUnitRateNo. thefacesidePVC filmwhichgoesaroundandwrapstheedges and		
	isbondedtotheedgesandthebacksidemetalizedpolyesterfilmsoastomak ethetilea completely sealed unit.		
	Providingandfixingaluminiumworkfordoors,windows,ventilatorsand partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions,i.e.attop,bottomandsideswith requiredEPDMrubber/neoprenegasketetc.Aluminiumsectionsshallbes mooth,rustfree, straight,mitredandjointedmechanicallywhereverrequiredincludingcleat angle,Aluminiumsnap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawingsandthedirectionsofEngineer-in- charge.(Glazing,panelinganddash fastenersto be paid for separately) Powdercoatedaluminium(minimumthicknessofpowdercoating50micro n)	Kg	33
33	Providingandfixing09mmthickprelaminatedparticleboardflatpressedthr eelayerorgraded woodparticleboardconformingtoIS:12823GradelTypell,inpanellingfixed inaluminumdoors, windowsshuttersandpartitionframeswithC.P.brass/stainlesssteelscrew setc.completeasper architecturaldrawingsanddirectionsofengineer-in- charge	Sqm	4.5
	Pre- laminatedparticleboardwithdecorativelaminationononesideandbalanci nglaminationon otherside		

34	Providingandfixingglazinginaluminiumdoor,window,ventilatorshuttersa ndpartitionsetc. with EPDM rubber / neoprene gasket etc.completeasperthearchitecturaldrawingsandthe directionsofengineer-in- charge.(Costofaluminiumsnapbeadingshallbepaidin basic item): Withfloatglasspanesof4.0mmthickness(weightnotlessthan10kg/sqm) ELECTRICALWORKII	Sqm	10
35	Wiring for light point/ fan point/ exhaust fan point/ call bell pointwith1.5sq.mmFRLSPVCinsulatedcopperconductor single core cable in surface / recessed medium class PVC conduit,withmodularswitch,modularplate,suitableGlbox and earthling the point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable etc. as required.	Point	11 Points
36	SteppedtypeModular Fanregulator(2 module) Wiring for light/ power plug with 2X4 sq. mm FRLS PVC insulated copper conductor single core cable in surface/ recessedmediumclassPVCconduitalongwith1No.4sq.mm	Each Meter	<u>3 Nos</u> 65
	FRLSPVCinsulatedcopperconductorsinglecorecableforloop earthing as required. S.P.5/6amps,onewaymodularswitch,ISImarked. S.P.15/16amps,onewaymodularswitch,ISImarked. 3pin5/6ampsmodularsocketoutlet,ISImarked. 6pin15/16ampsmodularsocketoutlet, ISImarked. Modular base & cover plate for 6 module	Each Each Each Each Each	8 8 8 8 8 8
37	Wiring for light/ power plug with 4X4 sq. mm FRLS PVC insulated copper conductor single core cable in surface/ recessedsteelconduitalongwith2Nos.4sq.mmFRLSPVC insulatedcopperconductorsinglecorecableforloopearthing as required.	Meter	15 RMT
38	Supplyingandfixing30A,415V,TPNIndustrialtypesocketoutlet,with4pole andearth, metal enclosed plug top along with 30 A "C" curve, TPNMCB, in sheet steel enclosure, on surface or in recess, with chained metal cover for the socket out let and complete with connections, testing and commissioning etc. as required. (5 Way)	Each	2 Nos
39	Supplyingandfixingof20- 36WLED2"X2"LEDlightfittings(Concealed)asrequiredat site.	Each	4 Nos
40	Supplyingandfixing ofCeilingFan asrequiredat site.	Each	3 Nos
41	SupplyingandFixingof250mmSizeExhaustFanasrequiredat site.	Each	2 Nos
42	Supplyingandfixingof200Ampsopentype4waycopperBusbarboxofsize 18"X18" with cable termination by using copper lugs.	Each	1 Set.
43	Supplying and fixing following way, single pole and neutral, sheetsteel,MCBdistributionboard,240V,onsurface/recess, complete with tinned copper bus bar, neutral bus bar, earth bar, din bar, interconnections, powder painted including earthing etc. as required. (But without MCB/RCCB/Isolator)	Each	1 No

	12way ,SingleDoor/Double door.		
44	Supplyingandfixing5Ato32Arating,240/415V,10kA,"C" curve, miniature circuit breaker suitable for inductive load of following poles in the existing MCB DB complete with connections, testing and commissioning etc. as required. 10ASinglepole 20 A Single pole	Each Each	2 Nos 2 Nos
	32ATP&N	Each	3 Nos
45	Supplyingandfixing of40 WLEDStreetlight fittingsoutdoor typeas requiredat site. Controlswitchfor theStreetlights hastobe providedout sidethe building.	Each	2 Nos
46	Supplyingandfixingfollowingrating,fourpole,415V,isolator in theexisting MCB DBcomplete with connections, testing and Commissioning etc. as required. 63 A	Each	4 Nos
47	Earthing with copper earth plate 600 mm X 600 mm X 3 mm thick including accessories, and providing masonry enclosure withcoverplatehavinglockingarrangementandwateringpipe of 2.7 metre long etc. with charcoal/ coke and salt as required.	Set	1 No
	Providing and laying earth connection from earth electrode with6SWGdiaG.I.Wirein15mmdiaG.I.pipefromearth electrodeincludingconnectionwithG.I.thimbleexcavationand re-filling as required.	Meter	12
48	Supplying and laying of fallowing sizes of PVC insulated Aluminumconductor wired Armored UG cable in DWC Pipe double walled corrugated high density poly ethylene pipe having corrugation on the outer wall 50 mm and plain surface inner wall of 55 mm sizes conforming to IS14930, with necessaryDWC fitting forprotection of1.1 KVgradeUGCable directly in ground at a depth of 2 feet including excavation and refilling the trench (including earthing and end termination) etc. as required at the site. (Vguard/Havel's/Polycab/AshirvadwithISI). 50sq mmx 3.5 core.	Mtrs	50 RMT

### Sd/-CHIEF ADMINISTRATIVE OFFICER